

Technical parameter	rs of 1500KW Perkins diesel generator set
Technical parameters of generator set:	
Unit model: XHY-1500GF/P	Steady state voltage regulation rate (%): ≤±1
Output power: 1500KW	Voltage fluctuation rate (%): ≤±0.5
Power factor: COSΦ=0.8	Transient voltage regulation rate (%): $+20 \sim -15$
Output voltage: 400V/230V	Voltage stabilization time (s) : ≤ 1
Output current: 2700A	Steady state frequency adjustment rate (%): ≤±1
Rated frequency: 50Hz	Frequency fluctuation rate (%): ≤±0.5
Rated speed: 1500rpm	Transient frequency adjustment rate (%): $+10\sim-7$
Fuel grade: 0# Light diesel	Frequency stabilization time $(S): \leq 3$
Overall dimension: 5800×2150×2550 (L×W×H mm	Fuel consumption (100%load): 208g/kW·h
Unit weight: 13000kg	Noise (LP7m): 108dB (A)
Fechnical parameters of diesel engine:	
Brand / origin: Perkins	Cooling mode: Closed water circulation cooling
Diesel engine model: 4016TAG1A	Oil supply mode: Direct injection
Diesel engine power: 1588KW	Control mode:: Electronic speed control
Number of cylinders / lifting structure: 16/V	Air inlet mode: Turbocharged & Intercooled
Bore stroke: 160×190mm	Overload capacity: 100%
Dil capacity: 213L	Displacement: 61.12L
Coolant liquid capacity: : 350L	Oil consumption rate: ≤0.25%
Start mode: DC24V Electric start	Speed: 1500rpm
Fechnical parameters of generator:	
Brand / origin: Xinhongyuan (Stanford Technology)	Insulation grade: H级
Motor model: HYF-1500	Degree of protection: IP23
Rated power: 1500kw	Wiring mode: Three phase four wire, Y-type connection
Rated voltage: 400V/230V	Regulation mode: AVR (Automatic voltage regulator)
Output frequency: 50Hz	Output factor: COSΦ=0.8
Rated speed: 1500rpm	Temperature rise: H(125 °C)

Ambient Temperatures: ≤40°C

The standard configuration of generator set is as follows:

Brand new water cooled engine (diesel);

Brand brushless alternators H class;

Altitude:: ≤1000m

Suitable for environment: 40 °C - 50 °C radiator water tank, belt driven cooling fan, fan safety shield;

Genset controller, battery floating charger;

Heave duty steel base-frame and vibration-damper;

Industrial Silencers and exhaust elbow;

Dry air filter, fuel filter, lubricating oil filter, starting motor and self charging generator;

Original technical documents of diesel engine and generator, instructions of , Operation & Maintenance manual etc.