

| Technical | parameters of 2000KW | Perkins | diesel | generator set |
|-----------|----------------------|---------|---------|----------------|
| | | | WICO CI | Echiciator set |

| Technical parameters of generator set: | | | | |
|---|--|--|--|--|
| Unit model: XHY-2000GF/P | Steady state voltage regulation rate (%): ≤±1 | | | |
| Output power: 2000KW | Voltage fluctuation rate (%): ≤±0.5 | | | |
| Power factor: COSΦ=0.8 | Transient voltage regulation rate (%): $+20 \sim -15$ | | | |
| Output voltage: 400V/230V | Voltage stabilization time $(s): \le 1$ | | | |
| Output current: 3600A | Steady state frequency adjustment rate (%): ≤±1 | | | |
| Rated frequency: 50Hz | Frequency fluctuation rate (%): \(\leq \pm 0.5 \) | | | |
| Rated speed: 1500rpm | Transient frequency adjustment rate (%): $+10 \sim -7$ | | | |
| Fuel grade: 0# Light diesel | Frequency stabilization time (S): ≤3 | | | |
| Overall dimension: 6000×2200×2700 (L×W×H mm) | Fuel consumption (100%load): 208g/kW·h | | | |
| Unit weight: 13500kg | Noise (LP7m): 108dB (A) | | | |
| Technical parameters of diesel engine: | | | | |
| Brand / origin: Perkins | Cooling mode: Closed water circulation cooling | | | |
| Diesel engine model: 4016-61TRG3 | Oil supply mode: Direct injection | | | |
| Diesel engine power: 1975KW/2173KW | Control mode:: Electronic speed control | | | |
| Number of cylinders / lifting structure: 16/V | Air inlet mode: Turbocharged & Intercooled | | | |
| Bore stroke: 160×190mm | Overload capacity: 100% | | | |

Oil capacity: 475L Displacement: 61.12L

Coolant liquid capacity: : 806L Oil consumption rate: ≤0.25%

Start mode: DC24V Electric start Speed: 1500rpm

Technical parameters of generator:

| Brand / origin: Xinhongyuan (Stanford Technology) | Insulation grade: H |
|---|---|
| Motor model: HYF-2000 | Degree of protection: IP23 |
| Rated power: 2000kw | Wiring mode: Three phase four wire, Y-type connection |
| Rated voltage: 400V/230V | Regulation mode: AVR (Automatic voltage regulator) |
| Output frequency: 50Hz | Output factor: COSΦ=0.8 |
| Rated speed: 1500rpm | Temperature rise: H(125 °C) |
| Altitude:: ≤1000m | Ambient Temperatures: ≤40°C |

The standard configuration of generator set is as follows:

Brand new water cooled engine (diesel);

Brand brushless alternators H class;

Suitable for environment: 40 °C - 50 °C radiator water tank, belt driven cooling fan, fan safety shield;

Genset controller, battery floating charger;

Heave duty steel base-frame and vibration-damper;

Industrial Silencers and exhaust elbow;

Dry air filter, fuel filter, lubricating oil filter, starting motor and self charging generator;

Original technical documents of diesel engine and generator, instructions of, Operation & Maintenance manual etc.